

Kitemark[®] Licence

No. KM 514535

The licence is granted to:

Pioneer Trading Company Essex Ltd Units 1-3 Red Barn, Warners Farm Howe Street Great Waltham Chelmsford CM3 1BN United Kingdom

In respect of:

BS 7412

Plastics windows made from PVC-U extruded hollow profiles

This issues the right and licence to use the Kitemark in accordance with the Kitemark Licence Conditions of Contract governing the use of the Kitemark, as may be updated from time to time by The British Standards Institution, and as approved by the Registrar under the Trade Marks Act 1994 (the "Conditions"). All defined terms in this Licence shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Licence provided at or from the above address.

Latest Issue: 24/02/2012

For and on behalf of BSI:

Gary Fenton, Global Assurance Director

First Issued: 26/07/2007





BSi



Kitemark® Licence

No. KM 514535

BS 7412:2002 Plastics windows made from unplasticized polyvinyl chloride (PVC-U) extruded hollow profiles.

This Licence covers the fabrication of windows from the range of profiles and components supplied by Synseal Extrusions Limited under Licence Number KM 30983.

System(s): Synerjy Suite PVC-U Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the

following controlled manual(s):

Syneriy Suite Technical Manual

Kitemarked Synseal Products List

System description: The windows are double glazed only, internally beaded only, multipoint

locking only, with welded transoms/mullions, tee and/or cruciform joints only.

Ventilation: None

Window Types: Casement windows

Tilt/turn windows Fixed windows

Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: **26/07/2007** Latest Issue: **24/02/2012** Page 2 of 5

raising standards worldwide[™]





Kitemark[®] Licence

No. KM 514535

Size Limitations and Performance Characteristics Synerjy Suite PVC-U Window System

Window Type	Length (up to a maximum of)	Height (up to a maximum of)	Perimeter (up to a maximum of)	Transom/Mullion length including frame (up to a maximum of)	Exposure category as given in Table 1 of BS 7412:2002			
Sash dimensions for approved casement sash profiles:								
Projecting top hung windows Reinforced	1156mm	1156mm	-	1	2000 Special			
Projecting side hung windows Reinforced	606mm	1356mm	-	-	2000 Special			
Sash dimensions for approved tilt/turn sash profiles:								
Tilt/turn windows Reinforced	1116mm	1416mm	-	-	1600 Special			
Overall dimensions for approved outer frame profiles:								
Fixed windows Part reinforced	2500mm	2500mm	8200mm	-	2400 Special			
Overall dimensions for approved transom/mullion profiles:								
Multilight windows, RS73 transom/mullion reinforcement	1800mm	1800mm	6000mm	1200mm	2000 Special			
Multilight windows, RS73 transom/mullion reinforcement	1400mm	1400mm	5400mm	1400mm	1600 Special			
Multilight windows, RS74 transom/mullion reinforcement	2400mm	2400mm	7800mm	1500mm	1600 Special			
Multilight windows, RS74 transom/mullion reinforcement	1400mm	1400mm	5400mm	1400mm	2000 Special			
Multilight windows, RS81 transom/mullion reinforcement	1600mm	1600mm	6400mm	1600mm	1600 Special			

First Issued: **26/07/2007** Latest Issue: **24/02/2012** Page 3 of 5

raising standards worldwide™



This Licence remains the property of The British Standards Institution and shall be returned immediately upon request. To check its validity telephone +44 (0)845 080 9000



Kitemark® Licence

No. KM 514535

This Licence covers the fabrication of windows from the range of profiles and components supplied by Synseal Extrusions Limited under Licence Number KM 30983.

System(s): Shield Suite PVC-U Window System

Fabrication and Installation:

Fabricated and installed in accordance with the latest issue(s) of the

following controlled manual(s):

Shield Technical Manual

Kitemarked Synseal Products List

System description: The windows are double glazed only, internally beaded only, multipoint

locking only, with welded transoms/mullions, tee and/or cruciform joints only.

Ventilation: None

Window Types: Casement windows

Tilt/turn windows Fixed windows

Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: **26/07/2007** Latest Issue: **24/02/2012** Page 4 of 5

raising standards worldwide™





Kitemark® Licence

No. KM 514535

Size Limitations and Performance Characteristics Shield PVC-U Window System

Window Type	Length (up to a maximum of)	Height (up to a maximum of)	Perimeter (up to a maximum of)	Transom/Mullion length including frame (up to a maximum of)	Exposure category as given in Table 1 of BS 7412:2002		
Sash dimensions for approved casement sash profiles:							
Projecting top hung windows Reinforced	1156mm	1156mm	-	-	2400 Special		
Projecting side hung windows Reinforced	606mm	1156mm	-	-	2400 Special		
Sash dimensions for approved tilt/turn sash profiles:							
Tilt/turn windows Reinforced	1116mm	1416mm	-	-	1600 Special		
Overall dimensions for approved outer frame profiles:							
Fixed windows Part reinforced	2500mm	2500mm	8200mm	-	2000 Special		
Overall dimensions for approved transom/mullion profiles:							
Multilight windows, RA71 transom/mullion reinforcement	1500mm	1500mm	6000mm	1500mm	1600 Special		
Multilight windows, RS73 transom/mullion reinforcement	1800mm	1800mm	6000mm	1200mm	2000 Special		
Multilight windows, RS73 transom/mullion reinforcement	1400mm	1400mm	5400mm	1400mm	1600 Special		
Multilight windows, RS74 transom/mullion reinforcement	2400mm	2400mm	7800mm	1500mm	1600 Special		
Multilight windows, RS74 transom/mullion reinforcement	1400mm	1400mm	5400mm	1400mm	2000 Special		

First Issued: **26/07/2007** Latest Issue: **24/02/2012** Page 5 of 5

raising standards worldwide[™]

BSi

This Licence remains the property of The British Standards Institution and shall be returned immediately upon request. To check its validity telephone +44 (0)845 080 9000